

Spirotrap® Drain 14", 16", 18" Dirt Separator

| |
|-----------------|
| Job Name: |
| Engineer: |
| Contractor: |
| Representative: |

| Tag | Model | Flow | Size | Location |
|-----|-------|------|------|----------|
| | | | | |

Specifications:

| | |
|----------------------------|----------|
| Shell | Steel |
| Coalescing Medium | Copper |
| Ball Valve | Brass |
| Max. Working Pressure | 150 psig |
| Max. Operating Temperature | 270°F |

Notes:
Removable lower head to facilitate cleaning if required.
(bc: Minimum bundle removal clearance)

| PS - Pipe Size | 14" | 16" | 18" |
|----------------|------|------|------|
| D (inches) | 28 | 32 | 36 |
| H (inches) | 61 | 69 | 78 |
| h (inches) | 44 | 49 | 56 |
| LF (inches) | 45 | 50 | 56 |
| DF (inches) | 37 | 42 | 46 |
| hs (inches) | 20 | 22 | 22 |
| e (inches) | 2 | 2 | 2 |
| bc (inches) | 45 | 47 | 55 |
| Weight (lbs) | 1510 | 2020 | 2600 |
| Rec Flow (gpm) | 2530 | 3300 | 4180 |
| Model | | | |
| TDN----FA | 1400 | 1600 | 1800 |

Bracket Detail

Bracket Detail

(Dimensions for reference only)

Fabricated and stamped in accordance with ASME, Section VIII, Division 1 for unfired pressure vessels.