

Spirotrap® Drain - Dirt Separator

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

Specifications:

Shell	Steel
Coalescing Medium	Copper
Ball Valve	Brass
Max. Working Pressure	150 psig
Max. Operating Temperature	270°F

Notes:
Removable lower portion to facilitate cleaning if required.
(bc: Minimum bundle removal clearance)

PS - Pipe Size	2"	2 ½"	3"	4"	5"	6"	8"	10"	12"
D (inches)	6.3	6.3	8.6	8.6	12.8	12.8	16.0	20.0	24.0
H (inches)	15.0	15.0	19.7	19.7	26.2	26.2	34.4	43.9	52.4
h (inches)	10.6	10.2	14.0	13.6	18.7	18.1	24.2	31.5	37.6
LF (inches)	15.2	15.7	20.2	20.6	27.7	27.7	33.6	37.5	42.5
DF (inches)	11	11	14	14	19	19	24	28	32
e (inches)	1	1	1	1	1	1	1	1	1
bc (inches)	8	8	10	10	16	16	22	28	33
Dry Weight (lbs)	93	135	178	187	302	328	596	925	1400
Volume (gallons)	1.3	1.3	4.5	4.5	13	13	28	56	93
Rec Flow (gpm)	60	90	140	240	370	540	940	1470	2090
Model									
TDN---FA	200	250	300	400	500	600	800	1000	1200

(Dimensions for reference only)

Flanged. ASME Section VIII, Division 1 Stamped and Registered