

Spirotrap® Junior Dirt Separator

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

	<p>Specifications:</p> <table border="1"> <tr> <td>Body</td> <td>Brass</td> </tr> <tr> <td>Ball Valve</td> <td>Brass</td> </tr> <tr> <td>Coalescing Medium</td> <td>Copper</td> </tr> <tr> <td>Press Fit Seal</td> <td>EPDM</td> </tr> <tr> <td>Max. Working Pressure</td> <td>150 psig</td> </tr> <tr> <td>Max. Operating Temperature</td> <td>270°F</td> </tr> </table> <p>Notes: Reverse Cap for Valve Handle</p>	Body	Brass	Ball Valve	Brass	Coalescing Medium	Copper	Press Fit Seal	EPDM	Max. Working Pressure	150 psig	Max. Operating Temperature	270°F
Body	Brass												
Ball Valve	Brass												
Coalescing Medium	Copper												
Press Fit Seal	EPDM												
Max. Working Pressure	150 psig												
Max. Operating Temperature	270°F												

Model	TDN075FT TDN075SW TDN075PF	TDN100FT TDN100SW TDN100PF	TDN125FT TDN125SW TDN125PF	TDN150FT TDN150SW TDN150PF	TDN200FT TDN200SW TDN200PF
d (Pipe Size NPT)	3/4"	1"	1 1/4"	1 1/2"	2"
D (inches)	2.6	2.6	2.6	2.6	4.0
H (inches)	4.6	5.6	6.3	7.9	9.6
h (inches)	3.8	4.3	4.8	6.3	8.0
L (FT) (inches)	3.3	3.5	3.5	3.5	5.2
L (SW) (inches)	4.1	4.5	4.5	4.7	6.9
L (PF) (inches)	6	6 1/4	6 3/4	6 3/4	9 1/2
e (valve) (inches)	1/2	1/2	1/2	1/2	1/2
Weight (lbs)	2.5	3.0	3.5	4.0	8.0
Rec. Flow (gpm)	6	10	15	30	40

(Dimensions for reference only)

Model Suffix: FT - Threaded NPT / SW - Sweat Connection / PF - Press Connection