

## Spirovent® Combi Air Eliminator and Dirt Separator with Magnet

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

**Specifications:**

Shell	Steel
Vent Head	Brass
Float	Non-Ferrous
Seal	Viton
O Ring	Viton
Skim Valve	Brass
Coalescing Medium	Copper
Magnets	Neodymium
Ball Valve	Brass
Max. Working Pressure	150 psig
Max. Operating Temperature	270°F

**Notes:**

DN – Pipe Size	2"	2 ½"	3"	4"	5"	6"
D (inches)	6.3	6.3	8.6	8.6	12.8	12.8
H2 (inches)	29.3	29.3	35.4	35.4	45.7	45.7
h2 (inches)	12.4	12.4	15.6	15.6	20.9	20.9
LF (inches)	15.2	15.7	20.2	20.6	27.7	27.7
e (inches)	1	1	1	1	1	1
x (inches)	3	3	3	3	3	3
y (inches)	3	3	3	3	3	3
Dry Weight (lbs)	76	85	149	159	248	270
Volume (gallons)	1.8	1.8	6.6	6.6	20	20
Rec. Flow (gpm)	60	90	140	240	370	540
Model						
VDT---FAM	200	250	300	400	500	600

(Dimensions for reference only)

Flanged ASME Section VIII, Division 1 Stamped and Registered