



**Submittal Data**  
VDX-1B-C

**Spirovent® Quad Microbubble™ Eliminator, Dirt Separator,  
Hydraulic Separator, Low Loss Header**

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

	<p><b>Specifications:</b></p> <table border="1"> <tr> <td>Body</td> <td>Brass</td> </tr> <tr> <td>Vent Head</td> <td>Brass</td> </tr> <tr> <td>Float</td> <td>Non-Ferrous</td> </tr> <tr> <td>Seal</td> <td>Viton</td> </tr> <tr> <td>O Ring</td> <td>Viton</td> </tr> <tr> <td>Coalescing Medium</td> <td>Copper</td> </tr> <tr> <td>Press Fit Seal</td> <td>EPDM</td> </tr> <tr> <td>Max. Working Pressure</td> <td>150 psig</td> </tr> <tr> <td>Max. Operating Temperature</td> <td>270°F</td> </tr> </table> <p><b>Notes:</b> Reverse Cap for Valve Handle</p>	Body	Brass	Vent Head	Brass	Float	Non-Ferrous	Seal	Viton	O Ring	Viton	Coalescing Medium	Copper	Press Fit Seal	EPDM	Max. Working Pressure	150 psig	Max. Operating Temperature	270°F
Body	Brass																		
Vent Head	Brass																		
Float	Non-Ferrous																		
Seal	Viton																		
O Ring	Viton																		
Coalescing Medium	Copper																		
Press Fit Seal	EPDM																		
Max. Working Pressure	150 psig																		
Max. Operating Temperature	270°F																		

Model	Unit	VDX100FT VDX100SW VDX100PF	VDX125FT VDX125SW VDX125PF	VDX150FT VDX150SW VDX150PF	VDX200FT VDX200SW VDX200PF
Pipe Size	inch	1	1-1/4	1-1/2	2
D	inch	3-1/8	3-1/8	3-1/8	4
H2	inch	20-1/4	20-1/4	20-1/4	30-1/4
h2	inch	7-3/8	7-3/8	7-3/8	8-1/4
h3	inch	5-3/8	5-3/8	5-3/8	10-1/4
L	inch	8-5/8	8-5/8	8-5/8	10-1/8
Weight	lbs	13.2	14.3	15.4	26.4
Rec. Flow	GPM	10	15	30	40

FT – Female Threads / SW – Sweat Connection / PF - Press Fit Connection